

Engine

XINCHAI
4D35ZG31 / 3.47L

Fuel type

Diesel

Load capacity @ 500 mm LC

4,500 kg



PT Thubas Liftindo Perkasa

PT Thubas Liftindo Perkasa

Head Office

Gang Wates Kp. Rawa Banteng No.102 Rt 003/01 Ds. Mekarwangi
Kec. Cikarang, Barat, Kabupaten Bekasi, Jawa Barat 17530

Branch Office

Bypass Pandaan, Jl. Raya Surabaya - Malang No.8, Sukorejo,
Karang Jati, Kec. Pandaan, Pasuruan, Jawa Timur 67156

Mobile : +62 878 4688 0298

Email : cs.thubaslifindoperkasa.com

Website : thubaslifindoperkasa.com

CPCD45

DIESEL
LOADER C
PNEUMATIC TIRES

 **LIUGONG**



Tough world. Tough equipment.

CPCD45 Specifications>>>

Are common	Model	1			CPCD45
	Fuel type	2			Diesel
	load capacity	3	With designated DH	kg	4,500
	Center of gravity	4		mm	500
Weight	Operating weight	5	without cargo	kg	6,570
	axle load	6	loaded front/rear	kg	9,820/3,000
		7	unloaded front/rear	kg	1.325/3.570
Tires	Tire type	8			Pneumatic
	wheels	9	front/rear		2/2
	Wheelbase	10		mm	2,100
	Tire size	eleven	front		8.25-15-14PR
		12	rear		7.00-12-12PR
Mast	Track width	13	front/rear		1.190/1.190
	Max. fork height	14	standard two-piece mast	mm	3,000
	free lift	15	standard two-piece mast	mm	190
	Height, mast down	16	standard two-piece mast	mm	2,285
	Height, mast raised	17	standard two-piece mast	mm	4,210
	Mast tilt forward/back	18	standard two-piece mast	deg	6°/ 12°
	Carriage	19	width	mm	1,400
	Fork span	20	minimum/maximum	mm	310/1,360
	Fork dimensions	21	T x W x D	mm	50x150x1.070
	Fork back length	22	standard two-piece mast	mm	3.208
Chassis	Overall width	23		mm	1.483
	Head Guard Height	24		mm	2.317
	turning radius	25	minimum external	mm	2,850
	Fork overhang	26	standard two-piece mast	mm	563
	Min. turning aisle width	27	cargo length and stock	mm	4,850
	Clearance	28	at minimum load	mm	165
		29	in the center of the wheelbase	mm	200
Performance	Travel speed	thirty	with/without load	km/h	24.5/25.5
	lifting speed	31	with/without load	m/s	550/580
	Lowering speed	32	with/without load	m/s	520/480
	Max. pulling force	33	loaded front/rear	kg	2,800
	max. gradeability	34	with load / without load	%	25/29.5
Systems	brakes	35	worker		Foot/pneumo-hydraulic booster
		36	parking lot		manual/mechanical
		37	manufacturer		xinchai
		38	model		4D35ZG31-008
	Engine	39	compliance with emission limit values		CHN Stage III
		40	cylinders		4
		41	engine capacity	liters	3.47
		42	power	kW/rpm	60/2,200
		43	Max torque	Nm/rpm	300/1,800

